

P211

5th Intel® Core™ i5-5200U

Intel® OPS Compliance

1*80-pin JAE connector

1*Intel® Gigabit Ethernet

Optional Mini PCIE WiFi&BT /3G module

Optional mSATAIII SSD

KEY FEATURES



Intel® Open Pluggable Specification

Simplify the device installation, usage, maintenance and upgrade of digital signage infrastructure.



Intel® Core™ i3/i5/i7 Processor

Rediscover what's possible with stunning visuals, enhanced security, and amazing power-saving.



Ultra HD

Pack around four times as many pixels into screens as existing HD sets, producing a sharper, higher-density picture.



HDMI 1.4a Output

Ultra High-definition video output (1080p, 2160p) and multi-channel digital audio.



Microsoft® DirectX® 11

Provides incredibly smooth and life-like graphics, including 3D. A must have for games and video enthusiasts.



Intel Gigabit LAN

High-speed LAN connection with 1Gb/s data transfer rate. Ideal for seamless internet connection for audio and video streaming.



Optional WiFi+Bluetooth® Module

Wireless solution (IEEE 802.11ac/b/g/n) to optimize your internet experience with speed and longer distance coverage. Bluetooth® to enable exchanging data over short distances.



USB3.0

Maximum transmission speed of up to 5Gb/s (10X faster than USB2.0), ideal for connecting to external hard drives.



COM Port

COM port for more device connect.



TPM (Trusted Platform Module)

TPM offers enhanced platform security through top level encryption; mandated by many IT departments.



Energy Saving

Low power consumption saves money and better for the environment.



RoHS Compliant

www.giadapc.nl



SPECIFICATIONS

Dimension	180mm * 119mm * 30mm (without the mounting frame) 200mm * 119mm * 30mm (include the mounting frame)
Processor	Intel® Core™ i3/i5/i7 Processor (Broadwell), Max. TDP 15W
Chipset	Integrated into CPU
Display	Intel® HD Graphics 5500 Microsoft® DirectX® 11,2 1x HDMI v1.4a with audio support
Memory	NA (1*SO-DIMM, up to 8G of DDR3L -1600 MHz (1.35V))
Storage	NA (2.5inch SATA III Type HDD or mSATAIII type SSD)
Audio	Realtek® High Definition Audio (5.1) Digital audio via HDMI connector 1x Audio out jack on the front panel 1x Mic in jack on the front panel
Ethernet	1x Intel® Gigabit Ethernet Controller(I218) 1x RJ45 port on the back panel
Wireless	NA (Optional IEEE802.11 ac/b/g/n+Bluetooth® module)
Expansion Slots	1x SIM Card slot for 3G 2x Mini-PCI Express® (Full-length for mSATAIII SSD; Full-length for PCIE/USB WiFi/BT/3G)
Peripheral interfaces	2x USB3.0+2x USB2.0 1x COM Port 1x JAE Port (1*HDMI+1*USB3.0+2*USB2.0+1*COM+1*Audio) 1x DC-IN jack (12V/19V)
Internal I/O Connectors	1x SATAIII 7+15Pin Port 1x SATAIII Port 1x SATA HDD Power Header 1x Auto Power On switch(default off) 1x DC_IN/OUT Header(2Pin)
OS Support	Windows® 7, Windows 8.1 & Linux
SystemBIOS	AMI EFI BIOS; ACPI
Cooler	Smart Fan
Operating Temperature	0°C to +40°C 32°F to 104°F
Accessories	1x Driver DVD Optional AC Adaptor Optional AC Power Cord Optional Docking Board

©2014-2015 Shenzhen JEHE Technology Development Co., Ltd., all rights reserved. Intel and Intel Core are trademarks of Intel Corporation in the U.S. and/or other countries. Windows is a trademark of Microsoft Corporation. All other trademarks are the property of their respective owners. Features, specifications, and appearance subject to change without notice.